# Local Triband Antenna GSM 900/1800/1900
## Order-No.:700-751-ANT01

The stationary antenna (Mini Base Station Antenna) is fastened on a mounting bracket for installation on vertical surfaces consideres in favourable transmission position. Likewise the antenna is suitable for external and internal areas.
A possible way in touch with repeaters is to be improve the field strength situation in public buildings, halls, underground garages, concrete/steel buildings, subways and so on decisive. In the near of radiator metallic surfaces should be avoid.

### Structural Construction:
The radiator is protected placed in a plastic tube.

### Electrical Parameters:

| | | | |
|---|---|---|---|
| Frequency ranges/MHz | 890 – 960 | 1710 – 1880 | 1880 – 1990 |
| *VSWR* | *≤ 2:1* | *≤ 2:1* | *≤ 2,2:1* |
| Gain | ≈2 dB | ≈2 dB | 0 dB |
| Impedance | 50Ω | 50Ω | 50Ω |
| Polarization | linear vertical | linear vertical | linear vertical |
| max. power | 20 W | 20 W | 20 W |
| Cable | 5 m* | 5 m* | 5m* |
| Connector | FME (f) | FME (f) | FME (f) |

*) Special cable with low attenuation „Low Loss“

Technical alterations reserved

**Systeme Helmholz** GmbH ● Gewerbegebiet Ost 36 ● 91085 Weisendorf
Phone: +49 9135 7380-0 ● Fax: +49 9135 7380-50 ● E-Mail: info@helmholz.de ● Internet: www.helmholz.de